



COMPACT PRESSURE TRANSDUCERS

ALL STAINLESS STEEL WETTED PARTS

PX481A Series

1 to 5 Vdc Output

Starts at
\$245



- ✓ Digitally Compensated for Excellent Total Accuracy and Interchangeability
- ✓ Gage, Absolute, Vacuum, and Compound Ranges Available
- ✓ Rugged, Compact Design
- ✓ RFI/EMI Protection
- ✓ 316L Stainless Steel Wetted Parts
- ✓ 1 to 5 V Output
- ✓ Cable and Connector Styles

OMEGA's PX481A Series transducers are designed for general industrial and commercial requirements and offer excellent performance in a wide range of applications. They are based on proven micro-machined silicon technology, providing high reliability, long-term stability, and low cost.

The PX481A is fully digitally compensated for the effects of pressure and temperature change. It is extremely accurate, with less than 0.3% FS reference accuracy and less than 1% FS over its compensated temperature range. Wetted parts are made of 316L stainless steel for a wide range of media compatibility.



PX481A-015G5V, \$245,
shown larger than actual size.



PX481AD-015G5V, \$255,
shown larger than actual size.

Color	Pin	WIRING:
Red	1	Ex +
Black	2	Common
White	3	Out +
Green	4	N/C

SPECIFICATIONS

Excitation: 9 to 30 Vdc

Output: 1 to 5 Vdc (3 wire)

Load Resistance: 50,000 Ω minimum

Accuracy: 0.3% BFSL maximum
(includes linearity, hysteresis and repeatability)

Operating Temperature:
-40 to 80°C (-40 to 176°F)

Compensated Temperature:
-25 to 75°C (-13 to 167°F)

Process Temperature:
-40 to 100°C (-40 to 212°F)

1-Year Stability: <0.25% FS

Proof Pressure: 2x FS

Burst Pressure: 3x FS

Wetted Parts: 316L stainless steel

Vibration: 10 g, 55 to 2000 Hz

Shock: 30 g

Process Connection: 1/8" NPT male

Electrical Connection: 18" 24-gage
cable or DIN 43650-A connector

Dimensions: 1 1/2" hex; 72 H x 29.7 mm
Dia. (2.84 x 1.17") [DIN connector adds
51 mm (2") to height]

Weight: 142 g (5 oz.)



COMPACT PRESSURE TRANSDUCERS



PX481AD-015G5V, \$255,
shown larger than actual size.

PX481A-015G5V, \$245,
shown larger than actual size.

ALL MODELS AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number)

GAGE PRESSURE RANGES

psi	bar	CABLE STYLE	PRICE	CONNECTOR STYLE	PRICE	COMPATIBLE METERS*
0 to 1	0 to 68.9 mbar	PX481A-001G5V	\$265	PX481AD-001G5V	\$275	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 6	0 to 413.7 mbar	PX481A-006G5V	245	PX481AD-006G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 15	0 to 1.0	PX481A-015G5V	245	PX481AD-015G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 30	0 to 2.1	PX481A-030G5V	245	PX481AD-030G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 60	0 to 4.1	PX481A-060G5V	245	PX481AD-060G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 100	0 to 6.9	PX481A-100G5V	245	PX481AD-100G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 200	0 to 13.8	PX481A-200G5V	245	PX481AD-200G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 300	0 to 20.7	PX481A-300G5V	245	PX481AD-300G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 500	0 to 34.5	PX481A-500G5V	245	PX481AD-500G5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 1000	0 to 69.0	PX481A-1KS5V	265	PX481AD-1KS5V	275	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 2000	0 to 138	PX481A-2KS5V	265	PX481AD-2KS5V	275	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 3000	0 to 207	PX481A-3KS5V	265	PX481AD-3KS5V	275	DP24-E, DP25B-E, DP41-E, DPi Series

VACUUM AND COMPOUND RANGES

0 to -15	0 to -1.0	PX481A-015VAC5V	\$245	PX481AD-015VAC5V	\$255	DP24-E, DP25B-E, DP41-E, DPi Series
-14.7 to 15	-1.0 to 1.0	PX481A-015C5V	245	PX481AD-015C5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
-14.7 to 30	-1.0 to 2.1	PX481A-030C5V	245	PX481AD-030C5V	255	DP24-E, DP25B-E, DP41-E, DPi Series
-14.7 to 60	-1.0 to 4.1	PX481A-060C5V	245	PX481AD-060C5V	255	DP24-E, DP25B-E, DP41-E, DPi Series

ABSOLUTE PRESSURE RANGES

0 to 15	0 to 1.0	PX481A-015A5V	\$265	PX481AD-015A5V	\$275	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 30	0 to 2.1	PX481A-030A5V	265	PX481AD-030A5V	275	DP24-E, DP25B-E, DP41-E, DPi Series
0 to 60	0 to 4.1	PX481A-060A5V	265	PX481AD-060A5V	275	DP24-E, DP25B-E, DP41-E, DPi Series

ACCESSORIES

MODEL NO.	PRICE	DESCRIPTION
PS-8E	\$10	Pressure snubber for water or light oils
PS-8D	10	Pressure snubber for dense liquids or oils
PS-8G	10	Pressure snubber for gases and steam
GE-0624	110	Reference Book: The Wiley Engineer's Desk Reference

* See section D for compatible meters.

Comes with complete operator's manual.

Ordering Example: PX481A-100G5V, 0 to 100 psig cable style transducer with 1 to 5 Vdc output, \$245.



VOLTAGE OUTPUT
PRESSURE TRANSDUCERS

B



UNITED STATES

www.omega.com

1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca

Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de

Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk

Manchester, England
0800-488-488

FRANCE

www.omega.fr

Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz

Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl

Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters